Flightcell DZM Specification

ingreen Dhi op	centeution			
Part number		FCDZ337RE2DIC - Civilian		
		FCDZ337RE2DIM - Mil	itary	
Material		Faceplate and backplate – machined from		
		aluminium 6061		
		Extrusion – aluminium	6061	
Input voltage		24-30 V DC		
Power supply current		Up to 250mA		
ICS transmit audio	Input	6mVrms to 5Vrms, adjustable		
	Input impedance	2700 Ω		
ICS receive audio	Output	53mVrms to 5Vrms		
	Output impedance	150 Ω		
Sat phone data connection		RS-232 levels. Settings configurable		
		for different phone typ	es	
Backlighting control		0-28V DC or 0-5V AC		
		Note that where an AC	lighting input is used that	
		is not referenced to DC	enced to DC ground, a suitable	
		isolating transformer should be used.		
Backlight colour		Green 540nm. Designed for		
		NVIS B compliance.		
Weight		750grams	26.5 oz	
Dimensions	Width	146mm	5.75"	
	Height	57mm	2.25"	
	Depth	130mm	5.1"	
GPS	Time to first fix	Typically 44s		
GPS Antenna	Connector	TNC		
	Bias Voltage	3V		
	Antenna Current	6-70mA		
	Typical gain	21dB		
Main connector		D38999/20WD35PN		
GPS connector		TNC		

Document revision 1.0 15/03/2010 FCN0054